

Hot Pad #1 Instructions

Things you will need:

- -Scissors
- -Tape Measure or Ruler
- -Decorative trim or ribbon
- -Fabric
- -Fleece or Insulated Fleece

Embroider the Design First

1. Cut your fabric to 9x9, this includes a ½ inch seam allowance. Using the same measurement cut a piece of fleece and a piece of fabric for the back.



2. Cut the fabric for the triangle top piece. Measure the width of the top and cut a perfect square with that measurement. Fold the Fabric from the bottom left corner to the upper right corner. Press the fabric and use the crease as a cut line. You now have two matching triangle pieces. Cut a piece of fleece that matches the two triangle pieces.



3. Place one triangle piece and the fleece together and pin them to the top of the main piece, right sides facing. Stitch with a ½ inch seam allowance.





4. Repeat step 3 with the main back piece and fleece.





 First pin your ribbon to the top for the loop, now pin decorative trim around the entire back piece. (This is optional) This will be sewn right side facing and turned right side out. Stitch around the trim to hold it in place.



6. Place the main front piece to the back piece, right side facing, pin in place. Leave an opening at the bottom for turning the fabric.



7. Turn the fabric right side out, fold in the opening and pin it in place. Hand stitch close. Press the hot pad to finish.



Your Hot pad is now complete!





Hot Pad #2 Instructions

Things you will need:

- Washable fabric pencil or marker
- Scissors
- Fabric
- 1/2" Double fold bias binding (or make your own)
- Fleece or Insulated Fleece
- Metal ring

First sew out the design.

1. Use a plate that is at least 9 inches wide, and use it as a template to cut out your fabric pieces.





2. Cut two pieces of matching fabric, and one fleece.



3. Using the same template, cut a smaller size for the back pocket. You can make the pocket any height you would like. Cut 2 matching pieces and a piece of fleece, whith this shape.



4. Using a ruler and a washable fabric pencil, draw a diamond pattern on the pocket, with the lines 2 inches apart.



5. Layer the two pocket pieces, with the fleece in the middle and pin around the edges.







- 6. Stitch around the outside of the pocket and along the drawn pencil lines.
- 7. Pin the binding to the top of the pocket and stitch in place.



8. Folding the binding around the top edge and sew in place.



 Layer the two main pieces with the fleece in the middle, and the pocket piece on the back. Pin around the edge, sew with ½ inseam.



10. Cut off any excess fabric.



11. Starting at the top of the hot pad, pin the binding in place and stitch.



12. Flip the hot pad over, and fold the binding around. Stitch in place. Leave a tail at the top for the loop.







13. Cut the excess tail to the size you want your loop to be. Fold in the bottom edge, pin in place and stitch for a finished edge.



14. Pin the loop binding and stitch up the side.



15. Add the metal ring, fold the binding to make a loop and stitch it to the back of the hot pad.



Your hot pad is now complete!







HOT PADS 15 Designs 5x7 Sewing Field 970663



Instructions included for 2 Hot Pad styles





